



## Technical Data

Solvent	Terpene
Propellant	Hydrocarbon
Coverage (approx.)	6m <sup>2</sup>
Spray pattern	Mist spray
Colour	Clear
Shelf life	12 months
Storage temperature	15°C - 35°C

## DASA DS-150 Aerosol

### Features

- Removes adhesive overspray
- Effectively removes most common spots and spills
- No rinsing required
- No sticky residue to cause re-soiling

### Properties & application

- A powerful, high performance, cleaning solvent, consisting of naturally occurring terpenes. **Citrus Cleaner** can be used as an alternative to cleaning solvents, such as mineral spirits, methyl ethyl ketone, acetone, toluene, glycol ethers, and fluorinated and chlorinated organic solvents.
- Has a high solvency and can be used to remove greases, oils, bitumen, resins, label adhesive residue, fluxes, adhesives and many other petrochemical based products..
- Non-reactive with metals and most types of plastics, but can degrade or swell some types of plastic and rubber. Always test a small sample of the material first to ensure the suitability of the product for the application. Do not use on expanded polystyrene.

**DO NOT USE ON FLEXIBLE PVC OR EXPANDED POLYSTYRENE.**

## Directions for use

1. Shake well before use.
2. Spray a small quantity of DS-150 onto an inconspicuous area of substrate to ensure compatibility. Do not use this product if the substrate discolours, softens or swells.
3. Spray product onto the soiled area and leave for 20-30 seconds, then remove with a soft lint free cloth.
4. For more stubborn stains, increase the product contact time, then rub vigorously with a soft lint free cloth or brush to remove the contaminant.
5. Repeat as necessary.

## Storage

Protect from extremes of temperature in a controlled environment between 15 and 35°C, and away from direct sunlight. Do not stand on a cold concrete floor. Low temperatures can result in irreparable separation of the adhesive. Stored under the correct conditions, in original, unopened containers, the product will have a shelf life of 12 months.

### **DO NOT ALLOW THE PRODUCT TO FREEZE**

### **Disclaimer**

All the information in the Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.

### **DASA International B.V.**

Bergerweg 62-M  
1815 AE Alkmaar  
The Netherlands

**Tel:** +31 72 571 99 17  
**Mail:** [info@dasa-international.com](mailto:info@dasa-international.com)  
**Web:** [www.dasa-international.com](http://www.dasa-international.com)

© 2023 DASA International B.V. Version 202307V1

All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.